



# BISON25 OTI



CONTROL PANELS:

BISON25 OTI — CP.BISON OTI p.133


## AUTOMATIONS FOR SLIDING GATES INDUSTRIAL USE

- control unit with built-in receiver, magnetic encoder and inverter
- oil submerged gear
- IP68 limit switch
- personalised release key
- up to 2,500 kg**



### 230 Vac

- Three phase 230 Vac geared motor, ventilated for intensive use
- Full metal mechanics and oil lubrication. The type of oil used ensures maximum efficiency even at low temperatures
- The encoder device ensures precision in the gate moving phases
- Casing protective treatment and paint
- The inverter technology allows for more precise adjustment of the gate moving phases, and increased crush prevention security
- Optional built-in FTC.S photocells, available as accessory




**RI.M4Z**  
9272030  
M4 galvanized rack (22x22x2000 mm).  
**Packaging: 2 pcs**



**RI.M6Z**  
9272040  
M6 galvanized rack 30x30x2000 mm. (needs the RI.P6 accessory to work).



**RI.P6**  
9630001  
M6 gear, It needs the rack RI.M6Z.



**FTC.S**  
9409089  
24Vac/dc surface mounting photocell. It is possible to synchronised up to 4 couple of photocells.



**RF.SUN**  
9409015  
Battery-operated device recharged by means of a photovoltaic panel applied on a mobile edge. (Technical features on p. 176)



**RF**  
9409016  
Device with a non rechargeable battery, with guaranteed duration 2 years. (Technical features on p. 176)



**SC.RF**  
9409014  
Device powered at 12/24 Vdc with self-test function and 2 outputs for connection to the electronic control panels. (Technical features on p. 176)



**ID.TA**  
9846019  
Warning board.

**MADE IN ITALY**

TECHNICAL DATA	BISON25 OTI
Code	9591449
Power supply	230 Vac (50-60Hz)
Motor supply	≈ 230 Vac
Max absorbed current	8 A
Max Thrust	2500 N
Opening speed	reg. 7-19 m/min
Operation cycle	intensive use
Protection level	IP44
Operating temperature	-20°C /+50°C
Lubrication	<b>OIL</b>
Max gate weight	2500 kg
Driving gear for rack	M4 Z18
Weight	31 kg
<b>Items no. per pallet</b>	<b>6</b>